



SEAT ADAPTOR KIT #88134 INSTALLATION INSTRUCTIONS




3727-01

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

ROADMASTER, Inc. 6110 NE 127th Ave. Vancouver, WA 98682 1-800-669-9690 fax 360-735-9300 www.roadmasterinc.com



- ## Parts List
- (1) 3/8" lock washer
 - (1) 3/8" x 3/4" bolt



Instructions

1. Before installing the seat adaptor, the mounting post (that was included with your BrakeMaster system) must be removed from the round plate (Fig.1). First, secure the round plate in a vise. Use a wrench to loosen the mounting post, while holding the bolt with an Allen wrench. Don't try to turn the Allen bolt with the Allen wrench, as you might damage the wrench or bolt. Use a 1/2" open-end wrench to twist the mounting post off. Then, secure the mounting post to the center of the seat adaptor, using the included 3/8" x 3/4" bolt and 3/8" lock washer.
2. Remove the two E10 Torx (6.8mm socket) seat track mounting bolts.
3. Now, place the seat adaptor between the floor and the seat tracks with the mounting post pointing towards the floor. *Note:* the side that measures 7 1/2" from the end to the mounting post goes towards the passenger side. Bolt the seat adaptor into place on each side with the bolts you removed in step 2.



WARNING

Failure to follow these instructions can result in property damage, personal injury or even death.