




SEAT ADAPTOR KIT #88251 INSTALLATION INSTRUCTIONS



3871-02

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

ROADMASTER, Inc. 6110 NE 127th Ave. Vancouver, WA 98682 1-800-669-9690 fax 360-735-9300 www.roadmasterinc.com



Parts List

- (1) 3/8" lock washer
- (1) 3/8" x 3/4" bolt
- (2) 10mm x 1.25 x 35mm bolts
- (2) 10mm flat washer
- (2) 10mm lock washer

Instructions

1. Before installing the seat adaptor, the mounting post (that was included with your BrakeMaster system) must be removed from the round plate (Fig.1). First, secure the round plate in a vise. Use a wrench to loosen the mounting post, while holding the bolt with an Allen wrench. Don't try to turn the Allen bolt with the Allen wrench, as you might damage the wrench or bolt. Use a 1/2" open-end wrench to twist the mounting post off. Then, secure the mounting post to the seat adaptor, using the included 3/8" x 3/4" bolt and 3/8" lock washer. *Note:* make certain you use the hole that lines up with the pedal.
2. Remove the 14mm factory bolts from the seat tracks. Now, place the seat adaptor over the seat tracks and bolt into place with the supplied 10mm x 1.25 x 35mm bolts, lock washers and flat washers.



WARNING

Failure to follow these instructions can result in property damage, personal injury or even death.