





SEAT ADAPTER KIT #88340 INSTALLATION INSTRUCTIONS



5912-00

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

ROADMASTER, Inc. 6110 NE 127th Ave. Vancouver, WA 98682 360-896-0407 fax 360-735-9300 www.roadmasterinc.com



Instructions

1. Locate the mounting post (Fig.1) that came with your BrakeMaster. If needed, order part number 450596. Now, secure the post to the seat adapter using the included 3/8" x 3/4" bolt and 3/8" lock washer (Fig.2). If the hole is countersunk, use the Allen head bolt and lock washer included with this kit.
2. Remove two Phillips screws attaching the plastic seat track cover to the seat track (Fig.3). *Note:* the seat track cover will not be replaced.
3. Remove two 18mm (head) seat track bolts (Fig.4).

continued on next page

Parts List

- (1) 3/8" lock washer
- (1) 3/8" x 3/4" bolt
- (2) 12mm x 1.25 x 80mm bolts
- (2) 12mm lock washers
- (2) 1/2" small flat washers
- (2) 1" O.D. x .188 wall pipe spacers

 1-800-669-9690

SEAT ADAPTER KIT #88340 INSTALLATION INSTRUCTIONS



5912-00

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

ROADMASTER, Inc. 6110 NE 127th Ave. Vancouver, WA 98682 360-896-0407 fax 360-735-9300 www.roadmasterinc.com



4. Place the supplied 1" O.D. x .188 wall pipe spacers over the holes you just exposed in the previous step (Fig.5).

5. Place the seat adapter over the pipe spacers and using the supplied 12mm x 1.25 x 80mm bolts, 12mm lock washers and 1/2" small flat washers, bolt down through each one and into the floor pan (Fig.6).

Note: make certain to position the adapter so that the mounting post is directly in line to the brake pedal. The BrakeMaster air cylinder may jam or function incorrectly if the mounting post is not directly in line with the brake pedal. Then, tighten all bolts.



6. Attach the BrakeMaster to the brake pedal and to the seat adapter. Adjust the length of the air cylinder assembly per the BrakeMaster installation instructions, ensuring that the BrakeMaster is pulling back on the brake pedal so the pedal is only depressed when the brakes are engaged at the motorhome. Failure to adjust the assembled length of the BrakeMaster may result in severe brake system damage and/or complete failure of the brakes.



WARNING

Failure to follow these instructions can result in property damage, personal injury or even death.